



Saturn®Fasteners, Inc.

an Acument® Global Technologies Company



Partial list of Saturn's SF Parts for OEM requirements

SF10-01	SF12-01	SF14-01	SF15-01	SF16-01
Bolt, 100-Deg Flush Head, Six Lobe Recess, Increased Short Thread (A-286 and 6al-4Titanium)	Screw, 100-Deg Flush Head, Six Lobe Recess, Full Thread (A-286 and 6AL-4V Titanium)	Bolt, 100-Deg Flush Head, Six Lobe Recess, Long Thread (A-286 and 6AL-4V Titanium)	Bolt, 100-Deg Flush Head, Six Lobe Recess, Increased Short Thread (Inconel 718)	Bolt, 100-Deg Flush Head, Six Lobe Recess, Long Thread (Inconel 718)
SF17-01	SF21	SF30	SF31	SF32-37A
Bolt, 100-Deg Flush Head, Six Lobe Recess, Increased Short Thread (Inconel 718)	Bolt, Tension, External Wrenching, 200,000 PSI Minimum Tensile Strength, For Cryogenic Applications (A-286 Per AMS 5726)	Screw 100-Deg Flat Head, Structural, (Low Carbon Steel)	Bolt, Hex Head Special, (A-286)	Bolt- Shear, Hex Head, (Alloy Steel Per Mil-S-5000)
SF33	SF34	SF35	SF36-101	SF38
Bolt, Hex Head Shoulder (A-286)	Screw, Machine, 100-Deg Flat Head, Six Lobe Recess, UNC-3A and UNF-3A	Screw, Machine, 100-Deg Flat Countersunk Head, Structural, Six lobe Recess UNC-3A and UNF-3A (Low Alloy Steel, Aluminum, A-286)	Bolt, Spindle-Rotor Hub Special For Bell Helicopter (PH 13-8 MO Per AMS5629)	Bolt, Tension, 220 KSI FTU, 900 Deg Fahrenheit, External Wrenching 12-Point, (H-11 Per AMS 6487)
SF39	SF40	SF41	SF42	SF43
Pin, Min Weapon Bay Door, Attachment, (PH13-8 MO, Titanium)	Screw, 100-Deg Flat Head, Full Thread, Self Locking & Non lockina. (Alloy Steel, A-286)	Bolt, Actuator Attach, Main Weapon Bay, (6AL-4V Titanium)	Bolt, Shear, 130-Deg Flat Head, Cruciform Recess, 95KSI Fsu.. (A-286, 6al-4V Titanium)	Bolt, Shear, 130-Deg Flat Head, Six Lobe Recess, 95 KSI Fsu., (A286, 6al-4V Titanium)
SF44	SF45	SF46	SF47	SF48
Screw, Electrode, Finish: Electropolish, (303 Stainless)	Spacer, Threaded, (Alloy Steel, 6AL-4V Titanium)	Bolt, Close Tolerance, 12-Point, Flange Head, 220 KSI FTU, Drilled & Un Drilled Head & Shank, (PH13-8 Mo)	Bolt, Close Tolerance, Double Hex Head, 125 KSI Shear, (PH13-8 MO)	Shear Pin, 12 Point Head, (A-286)
SF49	SF50	SF53	SF59	SF60
Shear Pin, 12 Point Head, (A-286)	Shear Pin, 12 Point Head, (A-286)	Bolt, Shear, 130-Deg Flush Head, 95 KSI Shear, For Composite Structures, (6AL-4V Titanium)	Bolt, Hex Head, 125 KSI Tensile, Drilled Head, (Alloy Steel, G4037, G8740)	Spacer, Threaded, (6AL-4V Titanium)
SF61	SF62	SF63	SF72	SF79
Bolt, Hex Head, Six Lobe Recess, Short Thread, (6AL-4V Titanium)	Pin, straight, Headed, Drilled Shank, (PH13-8Mo)	Internal Wrenching, Spline Drive Inconel	Flush Head Six-Lobe Short Thread (A-286)	Hex Head Shoulder Bolt Special Thread Length (A-286)
SFM11	SFM12	SF100-144	SF100-147	SFM10
Bolt, Machine, Hex Head, Fully Threaded, Fine Thread, Metric, Silver Plate (Steel, Property Class 10.9 Per ANSI B18.2.3.5M)	Bolt, Tension, Double Hexagon, Flanged, Metric, 1400 Mpa Minimum Tensile Strength, (A-286)	Pin, Index, Inlet, (Alloy Steel, ANSI 4140, ANSI 8740, ANSI 4340)	Pin-Stud, Protruding, Shear Head, (A-286)	Screw, Close Tolerance, 100-Deg Reduced Head, Six Lobe Recess, 660 Mpa Shear, Metrick (Alloy Steel, A-286, 6al-4V Titanium)